

Salient Features

- Homogeneous , hard wearing
- Random marbled pattern
- Anti bacterial / fungicidal
- PUR with Anti dirt surface minimizes scratches, scuff marks, stains and maintenance
- The flooring can be made seamless by way of thermal welding
- Application areas : hospital (Pre & post care), blood banks, pathology lab, clean rooms, pharmaceuticals (sterile and production area), food industry etc.

DIMENSIONS AVAILABLE

Thickness	2 mm
Roll width	1.50 mtr
Roll length	20 linear mtr
Tile size	305 mm x 305 mm

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	SYMBOLS	TEST METHOD	RESULTS
TOTAL WEIGHT		EN 430	3.2 KG/SQ. MTR FOR 2.0 MM
RESIDUAL INDENTATION AFTER STATIC LOAD		EN 433	≤ 0.10 MM
FLEXIBILITY LOW TEMPERATURE		EN 435	20 MM MANDREL, PASSED
DIMENSIONAL STABILITY		EN 434	≤ 0.4%
MARITIME USAGE			SUITABLE FOR MARITIME USE
CASTER CHAIR		EN 425	CONTINUOUS USE
HYGIENE CLEAN ROOM TEST		ISO 14644-1	TEST RESULT DEMONSTRATES THAT IT INHIBITS GROWTH OF MICROBES, CLASS A
ELECTROSTATIC PROPERTIES		EN 1815 EN 1081	DOES NOT ACCUMULATE CHARGES ABOVE 2KV $10^9\Omega$ - $10^{10}\Omega$
ABRASION RESISTANCE		EN 660-2 EN 649	WEAR GROUP T
SURFACE SPREAD OF FLAME		BS 476 PART 7	CLASS 1
FIRE PROPAGATION		BS 476 PART 6	(I)=10.8 } CLASS "O" (II)=1.7 }
SOUND ABSORPTION		ISO 140-8, EN ISO 717-2	Δ LW = 4DB
COLOUR FASTNESS TO DAY LIGHT		ISO 105-B02	>BLUE WOOL STANDARD 5
RESISTANCE TO CHEMICALS		EN 423	NO VISIBLE CHANGE
PERFORMANCE CLASSIFICATION		EN 685	34, 43